

# Selena family

Recess low glare downlight with excellent heat dissipation for longer life.



Selena-I

25° tilt  
recessed downlight  
or wall washing



Selena-II

Recessed downlight



Selena-III

25° tilt ultra low-glare  
recessed downlight  
or wall washing



Selena-IV

25° tilt ultra low-glare  
recessed downlight  
or wall washing



Selena-V

25° tilt  
recessed downlight  
or wall washing

## Standard Specification

Input power range\*: 6W, 10W, 15W, 20W

Efficacy (DALI-2): 85 lm/W @ 6W  
88 lm/W @ 10W  
102 lm/W @ 20W

Flicker-free driver (DALI-2): BK-PUL018A-0450Ad (12W)  
BK-PUL030A-0700Ad (20W, 30W)

Beam angle: 15°, 24°, 38° symmetrical

CRI: >95,

Colour temperature: Cool white, 5000K  
Neutral white, 4000K  
Warm white, 3000K

SDCM: 3

UGR: 10<19

LLD(Av): 2.21% @ 12,000 hrs

Lense: PPMA

Chromaticity shift (Av): 0.0012 @ 12,000 hrs

Fitting Material: pressed aluminium

Fitting colour: USA white

IP rating: IP51

Input Voltage: 180-264Vac

Power factor: >0.95@20W

Operating temperature: -20°C to 45°C

Approved standards: SAA, C-Tick

Life expectancy (L70): >100,000 hrs (Calc)  
>60,000 hrs ((Reported)

Luminaire warranty (L80): 5 yrs including driver

## Options

Lighting control system: wireless LoRa i3t

LoRa with i3t App system:

64,000 Lamp and device Nodes

Easy setup:

Simple point-n-click conventional zoning  
with optional multi-level grouping

0-100% zone or group dimming

Ambient light correction

Room correction factor

Occupancy sensing


Predictive control

Custom colour: Yes

Custom Dimensions: Yes

OEM integration: BacNet, KNX, Modbus,  
S-Mode, Desigo,  
Zen Control,  
Cognian Synchromesh

## Dimensions



Watts	Diam (d)	Cut-out (c)	Selena-I (h)	Selena-II (h)	Selena-III,IV (h)	Selena-V (h)
6W	65	55	91	-	-	-
10	86	75	90	90	106	88
15	113	100	90	90	-	-
20	113	100	134	110	-	-

All dimensions in mm  
Watts can be reduced

### Ordering Information

Note: New part number, all else unchanged

DLSab-cd-ef-g

a:	Luminaire Wattage.	e.g. DLS <b>20</b> ... = 20W	d:	1 (55), 2 (75), 3 (100), Selena cut-out in mm
b:	Standard driver, DALI-2 driver, Tunable driver		e:	Lora i3t, Blank (no LoRa)
c:	Cool white, Neutral white, Tunable		f:	PIR, Microwave, Combine PIR, Abient and Daylight sensors Blank (no sensor). Sensors are external from fitting.
			g:	IPxx, Blank (54)